

Specifications Model 10620 Crane  
**SPECIFICATION SHEET**

Crane Rating:	55,000 ft-lbs (7.60 ton-meters)
Standard Boom Length:	11' 0"(3.35 m) from CL of Crane
Boom Extension:	1st stage: Hydraulic 60"(152.4 cm) 2nd stage: Hydraulic 60"(152.4 cm)
Maximum Horizontal Reach:	20'-9"(6.32 m) from CL of Crane
Maximum Vertical Lift:	22'(6.71 m)
(from crane base)	
Boom Elevation:	-5 to +80 degrees
Stowed Height (crane only)	34" (86.4 cm)
Mounting Space Required	21 x 25 inches (53.3 x 63.5 cm)
Approximate Shipping Weight	2150 lbs (975 kg)
Controls	Radio control standard for all functions.
Winch Specification	
Rope Diameter:	7/16" (1.11 cm)
Line pull speed:	60 ft/min (18.29 m/min)
Max. single part line:	5000 lbs (2268 kg)
Max. double part line:	10000 lbs (4535 kg)
Rotation: (worm gear)	400 degree power
Lifting Capacities	10,000 lbs @ 5'0"(4535 kg @ 1.52m) 5100 lbs @ 11'0"(2315 kg @ 3.35m) 4285 lbs @ 13'6"(1940 kg @ 4.11m) 3475 lbs @ 16'0"(1575 kg @ 4.88m) 3060 lbs @ 18'6"(1385 kg @ 5.64m) 2650 lbs @ 21'0"(1200 kg @ 6.40m)
Power Supply Required	PTO & Pump (8 gpm @ 2800 psi)

\*Subject to change without notification