

Specifications Model 10629 Crane
SPECIFICATION SHEET

Crane Rating:	60,000 ft-lbs (8.29 ton-meters)
Standard Boom Length:	13'0"(3.96 m) from CL of Crane
Boom Extension:	1st stage: Hydraulic 96"(243.8 cm)
	2nd stage: Hydraulic 96"(243.8 cm)
Maximum Horizontal Reach:	29'0"(8.84 m) from CL of Crane
Maximum Vertical Lift:	30'6"(9.29 m)
(from crane base)	
Boom Elevation:	-5 to +80 degrees
Stowed Height (crane only)	34" (86.4 cm)
Mounting Space Required	21 x 25 inches (53.3 x 63.5 cm)
Approximate Shipping Weight	2900 lbs (1315 kg)
Controls	Radio control standard for all functions.
Winch Specification	
Rope Diameter:	7/16" (1.11 cm)
Line pull speed:	60 ft/min (18.29 m/min)
Max. single part line:	5000 lbs (2268 kg)
Max. double part line:	10000 lbs (4535 kg)
Rotation: (worm gear)	400 degree power
Lifting Capacities	10,000 lbs @ 5'0"(4535 kg @ 1.52m)
	4875 lbs @ 13'0"(2210 kg @ 3.96m)
	3910 lbs @ 17'0"(1770 kg @ 5.18m)
	2950 lbs @ 21'0"(1335 kg @ 6.40m)
	2530 lbs @ 25'0"(1147 kg @ 7.62m)
	2115 lbs @ 29'0"(960 kg @ 8.84m)
Power Supply Required	PTO & Pump
	(8 gpm @ 2800 psi)

*Subject to change without notification