

Specifications Model 12629 Crane
 SPECIFICATION SHEET

Crane Rating:	66,000 ft-lbs (9.12 ton-meters)
Standard Boom Length:	13'0"(3.96 m) from CL of Crane
Boom Extension:	1st stage: Hydraulic 96"(243.8 cm) 2nd stage: Hydraulic 96"(243.8 cm)
Maximum Horizontal Reach:	29'0"(8.84m) from CL of Crane
Maximum Vertical Lift:	30'6"(9.29m)
(from crane base)	
Boom Elevation:	-5 to +80 degrees
Stowed Height (crane only)	34" (86.4 cm)
Mounting Space Required	21 x 25 inches (53.3 x 63.5 cm)
Approximate Shipping Weight	2975 lbs (1350 kg)
Controls	Radio control standard for all functions.
Winch Specification	
Rope Diameter:	7/16" (1.11 cm)
Line pull speed:	60 ft/min (18.29 m/min)
Max. single part line:	6000 lbs (2725 kg)
Max. double part line:	12000 lbs (5440 kg)
Rotation: (worm gear)	400 degree power
Lifting Capacities	12,000 lbs @ 5'0"(5440 kg @ 1.52m) 5125 lbs @ 13'0"(2325 kg @ 3.96m) 4150 lbs @ 17'0"(1885 kg @ 5.18m) 3175 lbs @ 21'0"(1440 kg @ 6.40m) 2745 lbs @ 25'0"(1245 kg @ 7.62m) 2310 lbs @ 29'0"(1050 kg @ 8.84m)
Power Supply Required	PTO & Pump (8 gpm @ 2800 psi)

*Subject to change without notification