

Specifications Model 6620 Crane
SPECIFICATION SHEET

Crane Rating:	38,000 ft-lbs (5.25 ton-meters)
Standard Boom Length:	11' 0"(3.35 m) from CL of Crane
Boom Extension:	1st stage: Hydraulic 60"(152.4 cm)
	2nd stage: Hydraulic 60"(152.4 cm)
Maximum Horizontal Reach:	20'-9"(6.32 m) from CL of Crane
Maximum Vertical Lift:	22'(6.71 m)
(from crane base)	
Boom Elevation:	-5 to +80 degrees
Stowed Height (crane only)	32.5" (82.6cm)
Mounting Space Required	21 x 25 inches (53.3 x 63.5 cm)
Approximate Shipping Weight	1625 lbs (735 kg)
Controls	Radio control standard for all functions.
Winch Specification	
Rope Diameter:	3/8" (.953 cm)
Line pull speed:	60 ft/min (18.29 m/min)
Max. single part line:	3000 lbs (1360 kg)
Max. double part line:	6000 lbs (2720 kg)
Rotation: (worm gear)	400 degree power
Lifting Capacities	6,000 lbs @ 5'0"(2720 kg @ 1.52m)
	3525 lbs @ 11'0"(1600 kg @ 3.35m)
	2960 lbs @ 13'6"(1345 kg @ 4.11m)
	2400 lbs @ 16'0"(1090 kg @ 4.88m)
	2110 lbs @ 18'6"(960 kg @ 5.64m)
	1825 lbs @ 21'0"(830 kg @ 6.40m)
Power Supply Required	PTO & Pump
	(8 gpm @ 2800 psi)

*Subject to change without notification