



**50/50/100
Lube Skid**

50/50/100 Gallon New Oil & Waste Oil Product Tank consisting of the following:

2 Air operated new 5:1 oil pumps with ½" x 50' delivery hose and "Lincoln" spring rewind reel, metered nozzle, and installation plumbing to two approximately 50 gallon sections of the compartment tank with the following:

- All A-36 hot-rolled steel construction.
- 10 gallon formed shell with inserted ends.
- Lap welded seams inside and out with metal core wire.
- App. 32" long x 48" wide x 34" tall.
- Two each 2" threaded fill opening.
- Vented fill caps
- Quick release system with lifting lugs.
- Single air connection for customer provided air system

Air Driven Waste Oil Evacuation System:

- Air operated "LINCOLN" 1" aluminum double diaphragm pump
- On-load / off-load through single hose with manual transition valve
- "Lincoln" spring rewind hose reel with ¾" x 25' suction hose, terminated with ball valve and extension tube
- 2" threaded fill opening.
- Vented fill cap
- 100 Gal. waste oil storage tank
- Filter / regulator / oiler on input air line

Air Driven New Oil System:

- Lincoln 5:1 air operated reciprocating pump
- “Lincoln” spring rewind hose reel with ½” x 50’ delivery hose, terminated with Lincoln 877 metered nozzle
- 2” threaded fill opening.
- Vented fill cap
- 2 - 50 Gallon storage tanks