



Quad 60 Poly Lube Skid

General Construction:

- Fabricated steel skid constructed of structural steel tubing and 3/16" mild sheet steel with a 12 gauge steel floor
- Rear facing reel rack
- Molded polyethylene constructed product tanks
 - Not compatible with diesel or gasoline fuels
- Four corner lifting provisions
- Understructure fork lift provisions
- Air operated lube systems individually controlled w/ ball valves
- Air supplied to single bulkhead located at rearmost corner of lube skid

Lube Systems

- **60 gallon new oil system**
 - Lincoln 5:1 air operated reciprocating pump
 - Plumbed through Force America new oil filter to Hannay 1/2" x 50' spring rewind hose reel, terminated with Lincoln 912EF metered nozzle
 - Includes provisions for remote fill, accessible from rear of lube skid
- **60 gallon antifreeze system**
 - Lincoln 1/2" aluminum diaphragm pump
 - Plumbed to Hannay 1/2" x 50' spring rewind hose reel, terminated w/ Lincoln water bibb nozzle
 - Include provisions for remote fill, accessible from rear of lube skid
- **60 gallon used oil system**
 - Lincoln 1" aluminum diaphragm pump
 - Lincoln 1" directional valve to allow single line suction/discharge of used oil
 - Plumbed to Hannay 3/4" x 25' spring rewind hose reel, terminated w/ 3/4" ball valve and 4" suction tube